

Safety Data Sheet
AG-2001

SECTION I - IDENTIFICATION

PRODUCT NAME: AG-2001

PRODUCT USE: High Pressure, Non-Melt Red Grease
COMPANY NAME: Continental Research Corporation
COMPANY ADDRESS: PO Box 15204 St. Louis MO 63110
COMPANY PHONE: 800-325-4869
EMERGENCY PHONE: 888-255-3924 (CHEM-TEL)

SECTION II – HAZARDS IDENTIFICATION

CLASSIFICATION: Flammable Aerosol: Category 1
Liquefied Gas
Skin Irritant: Category 2
Eye Irritant: Category 2b
Carcinogenicity: Category 2
Specific Target Organ Toxicity (Single Exposure): Category 3
Aspiration Hazard: Category 1

HAZARD STATEMENT(S): **DANGER:** Extremely Flammable Aerosol Contains gas under pressure: May explode if heated. Causes skin and eye irritation. Suspected of causing cancer. May cause drowsiness and dizziness. May be fatal if swallowed and enters airways.

This product contains the following percentage of chemicals of unknown toxicity: 28%

PRECAUTIONARY STATEMENTS: Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50C/122F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves. Avoid breathing fumes, vapors, and spray. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. If exposed or concerned: Get medical advice or attention. Store locked up. Dispose of contents and container in accordance with local, state, and national regulations.



SYMBOL:

HAZARDS NOT OTHERWISE CLASSIFIED: N/A

SECTION III – COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS NUMBER	PERCENT
Heptane	142-82-5	10-30%
Hydrotreated Heavy Naphthenic Petroleum Distillate	64742-52-5	15-40%
Propane/n-Butane	68476-86-8	10-30%
Tetrachloroethylene	127-18-4	10-30%

SECTION IV - FIRST AID MEASURES

EYES: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

INGESTION: Seek medical attention immediately, rinse mouth out with water, drink 2 glasses of water, and induce vomiting immediately as directed by medical personnel.

INHALATION: Move to fresh air. If breathing is difficult or unconscious, administer oxygen. If not breathing administer artificial respiration. Seek medical attention if irritation persists.

SKIN: If on skin: Wash with plenty of water. If skin irritation occurs: get medical attention.

ACUTE HEALTH HAZARDS: Eyes: redness, tearing, blurred vision

Skin: defatting and dermatitis

Safety Data Sheet
Bodacious VOC Compliant

Inhalation: Anesthetic, irritation, Central Nervous System depression

Oral: abdominal irritation, nausea, vomiting, diarrhea, aspiration risk

CHRONIC HEALTH HAZARDS: Possible cancer causing agent and overexposure may also include damage to kidneys, liver, dizziness, headache, nausea, mental confusion, visual disturbances, dermatitis, lungs, blood, or central nervous system.

NOTE TO PHYSICIAN: Do not administer adrenaline or epinephrine to a victim of chlorinated solvent poisoning. This product contains ingredients that may be anticipated to be a carcinogen.

SECTION V – FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: Dry chemical, foam, or Carbon Dioxide (CO₂).

UNSUITABLE EXTINGUISHING MEDIA: Water spray/stream.

SPECIAL FIRE FIGHTING PROCEDURES: Wear full protective clothing and NIOSH approved SCBA with full facepiece operated in positive pressure or pressure demand. Use water mist to keep material cool in fire situations.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Keep away from sparks, open flames, and hot surfaces. No smoking. Do not spray on an open flame or other ignition source.

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon, hydrogen chloride gas, and Phosgene under forced combustion.

SECTION VI – ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTIVE EQUIPMENT: Refer to section VIII for proper Personal Protective Equipment.

SPILL: Remove sources of ignition such as pilot lights. Material is heavier than air and can settle in low lying areas in flammable concentrations, ventilate area. Product will undergo rapid evaporation. Use absorbent on spill sweep to clean. Small releases may be wiped up with wiping material. Dispose in accordance with local, state and federal laws.

WASTE DISPOSAL: Dispose of in accordance with federal, state, and local regulations.

RCRA STATUS: Waste solvent likely considered U210 (Tetrachloroethylene) under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION VII – HANDLING AND STORAGE

HANDLING AND STORAGE: Pressurized container: Do not pierce or burn, even after use. Store locked up. Protect from sunlight. Store in a well ventilated place. Do not expose to temperatures exceeding 50°C/122°F. Store locked up.

OTHER PRECAUTIONS: Use gloves, lab coat or apron, splash goggles, and use a vapor respirator approved/certified respirator or equivalent when ventilation is not adequate.

INCOMPATIBILITY: Strong acids, strong alkalis, strong oxidizing agents, chemically active metals, such as aluminum, barium, lithium, sodium, magnesium, potassium, titanium, beryllium, concentrated nitric acid some plastics, rubbers, and coatings.

SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
Heptane	500 ppm	400 ppm
Hydrotreated Heavy Naphthenic Petroleum Distillate	5 mg/m ³	5 mg/m ³
Propane/n-Butane	1000 ppm	1000 ppm
Tetrachloroethylene	25 ppm	25 ppm

ENGINEERING CONTROLS / VENTILATION: Use only outdoors or in a well-ventilated area.

RESPIRATORY PROTECTION: If exposure levels are exceeded then organic vapor cartridge respirator or SCBA will be needed.

PERSONAL PROTECTIVE EQUIPMENT: Safety glasses and chemical resistant gloves

ADDITIONAL MEASURES: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Red Viscous Spray

ODOR: Petroleum odor

ODOR THRESHOLD: N/D

BOILING POINT: N/D

FREEZING POINT: N/D

Safety Data Sheet
AG-2001

FLAMMABILITY: Extremely Flammable Aerosol
FLASH POINT: N/D
AUTOIGNITION TEMPERATURE: N/D
LOWER FLAMMABILITY LIMIT: N/D
UPPER FLAMMABILITY LIMIT: N/D
VAPOR PRESSURE (mm Hg): N/A
VAPOR DENSITY (AIR=1): N/A
EVAPORATION RATE: N/D
SPECIFIC GRAVITY (H₂O=1): 0.93
pH: N/A
SOLIDS (%): 28%
SOLUBILITY IN WATER: 0%
PARTITION COEFFICIENT: n-OCTANOL/WATER (K_{ow}): N/D
VOLATILITY INCLUDING WATER (%): 70.5%
VOLATILE ORGANIC COMPOUNDS (VOC): 48%
DIELECTRIC STRENGTH (Volts): N/D
DECOMPOSITION TEMPERATURE: N/D
VISCOSITY: N/D

SECTION X – STABILITY AND REACTIVITY DATA

REACTIVITY: Chemically active metals and bases.

CHEMICAL STABILITY: Stable

CONDITIONS TO AVOID: Temperatures greater than 122°F and sources of ignition.

INCOMPATIBILITY: Strong acids, strong alkalis, strong oxidizing agents, chemically active metals, such as aluminum, barium, lithium, sodium, magnesium, potassium, titanium, beryllium, concentrated nitric acid some plastics, rubbers, and coatings.

HAZARDOUS DECOMPOSITION OR BY-PRODUCT: Oxides of carbon, Hydrogen Chloride gas, and Phosgene.

POSSIBLE HAZARDOUS REACTIONS: None Known

SECTION XI – TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: Tetrachloroethylene (127-18-4) LD₅₀ (Oral, Rat) 2629 mg/kg; LD₅₀ (Dermal, Rabbit) > 3228 mg/kg; LD₅₀ (IPR, Mouse) 4700 mg/kg; LC₅₀ (Inhalation, Mouse, 4hr) 5200 ppm; LC₅₀ (Inhalation, Rat, 8hr) 34200 mg/m³

ROUTES OF ENTRY: Eyes, Ingestion, Inhalation, Skin

EYES: Strong Irritation likely, redness, visual disturbance, and pain. May cause eye damage

INGESTION: Nausea, vomiting, headaches, abdominal pain, diarrhea, dizziness, tremor, drowsiness, pulmonary edemas, absorption through the gastrointestinal tract may produce symptoms of CNS depression ranging from unconsciousness to death.

INHALATION: Irritation to respiratory tract, dizziness, headache, nausea, depression of central nervous system, prolonged exposure may cause unconsciousness, heart effects, liver effects, kidney effects, and death.

SKIN: Irritation likely, redness and pain. May cause localized defatting, blistering with prolonged skin contact. May be absorbed through the skin.

MEDICAL CONDITION AGGRAVATED: Excessive exposure will aggravate pre-existing disorders of eyes, skin, respiratory, liver, kidney, cardiovascular system, pulmonary illnesses, or central nervous system.

ACUTE HEALTH HAZARDS: Eyes: redness, tearing, blurred vision

Skin: defatting and dermatitis

Inhalation: Anesthetic, irritation, Central Nervous System depression

Oral: abdominal irritation, nausea, vomiting, diarrhea, aspiration risk

CHRONIC HEALTH HAZARDS: Possible cancer causing agent and overexposure may also include damage to kidneys, liver, dizziness, headache, nausea, mental confusion, visual disturbances, dermatitis, lungs, blood, or central nervous system.

CARCINOGENICITY: OSHA: Yes ACGIH: A3 - Animal Carcinogen NTP: 2 - Anticipated

IARC: 2A - Probable OTHER: CA Prop 65

SECTION XII – ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: Tetrachloroethylene - 127-18-4 - Ecotoxicity in water (LC50): 18.4 mg/l 96 hours [Fish (Fathead Minnow)]. 18 mg/l 48 hours [Daphnia (daphnia)]. 5 mg/l 96 hours [Fish (Rainbow Trout)]. 13 mg/l 96 hours [Fish (Bluegill sunfish)].

BIODEGRADABILITY: Component or components of this product are not biodegradable.

Safety Data Sheet
Bodacious VOC Compliant

BIOACCUMULATION: This product is not expected to bioaccumulate.

SOIL MOBILITY: This product is mobile in soil.

OTHER ECOLOGICAL HAZARDS: This material is toxic to aquatic life.

SECTION XIII – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Dispose of in accordance with federal, state, and local regulations.

RCRA STATUS: Waste solvent likely considered U210 (Tetrachloroethylene) under RCRA, however product should be fully characterized prior to disposal (40 CFR 261).

SECTION XIV - TRANSPORTATION INFORMATION

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.

HAZARD CLASS/DIVISION: 2.1 (6.1)

UN/NA NUMBER: UN 1950

PACKAGING GROUP: N/A

AIR SHIPMENT

PROPER SHIPPING NAME: Forbidden by USDOT Regulations

HAZARD CLASS/DIVISION: N/A

UN/NA NUMBER: N/A

SHIPPING BY WATER:

VESSEL (IMO/IMDG)

PROPER SHIPPING NAME: Aerosols, Ltd. Qty.

HAZARD CLASS/DIVISION: 2.1 (6.1)

UN/NA NUMBER: UN 1950

ENVIRONMENTAL HAZARDS WATER: Marine Pollutant

SECTION XV - REGULATORY INFORMATION

TSCA STATUS: All Chemicals are listed or exempt.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): Tetrachloroethylene (127-18-4)
Reportable Quantity = 100 lbs

SARA 311/312 HAZARD CATEGORIES: Acute, Chronic, Flammable, Carcinogen

SARA 313 REPORTABLE INGREDIENTS: Tetrachloroethylene (127-18-4)

STATE REGULATIONS: California Prop 65 - Tetrachloroethylene is known to the state of California to cause cancer.

Tetrachloroethylene - Massachusetts Right To Know, Pennsylvania Right To Know, New Jersey Right To Know, Heptane -
Massachusetts Right To Know, Pennsylvania Right To Know, New Jersey Right To Know

INTERNATIONAL REGULATIONS: All components of this product are on the Canadian DSL list.

NFPA HEALTH: 2

HMIS HEALTH: 2

NFPA FLAMMABILITY: 3

HMIS FLAMMABILITY: 3

NFPA REACTIVITY: 0

HMIS REACTIVITY: 0

NFPA OTHER: None

HMIS PROTECTION: B

SECTION XVI - ADDITIONAL INFORMATION

PREPARATION BY: EHS Administrator

DATE PREPARED: 01/06/2014

REVISION DATE: 11/24/2014

N/A = Not Applicable; N/D = Not Determined

DISCLAIMER: To the best of our knowledge, information contained herein is accurate. However there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or

Safety Data Sheet

AG-2001

accuracy. Since the conditions of handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.